

EnviroSAND^{plus} Installation Specifications

Coverage Rates per Bag

Minimum Joint Width:	1/8"
Maximum Joint Width:	3/8"

Minimum Paver Depth:	2"
Uncompacted Dry Density:	1.5g/cm ³

Paver Dimension	Coverage Rate (ft ² /bag)			
	Paver Depth = 2" (50mm) Joint Width = 1/8"	Paver Depth = 2" (50mm) Joint Width = 3/8"	Paver Depth = 2-3/8" (60mm) Joint Width = 1/8"	Paver Depth = 2-3/8" (60mm) Joint Width = 3/8"
2" x 2"	33.95	11.32	28.29	9.43
4" x 4"	63.95	21.32	53.29	17.76
6" x 6"	94.83	31.61	79.02	26.34
8" x 8"	125.00	41.67	104.17	34.72
4" x 8"	84.62	28.21	70.51	23.50

Application Requirements

Minimum Joint Width:	1/8"
Maximum Joint Width:	3/8"

Minimum Paver Depth:	2"
Uncompacted Dry Density:	1.5g/cm ³

Paver Dimension	Coverage Rate (lbs/ft ²)			
	Paver Depth = 2" (50mm) Joint Width = 1/8"	Paver Depth = 2" (50mm) Joint Width = 3/8"	Paver Depth = 2-3/8" (60mm) Joint Width = 1/8"	Paver Depth = 2-3/8" (60mm) Joint Width = 3/8"
2" x 2"	1.62	4.86	1.94	5.83
4" x 4"	0.86	2.58	1.03	3.10
6" x 6"	0.58	1.74	0.70	2.09
8" x 8"	0.44	1.32	0.53	1.58
4" x 8"	0.65	1.95	0.78	2.34

* Application rates for Envirobond jointing materials closely match standard jointing sand application rates.

** Coverage Rates are estimated based on standard paver sizes. For unique paving systems, contact the paver manufacturer to determine specific jointing material requirements.

